

The **INGRESS'R**

A 36" pillar of
AccessAbility™

for all
pedestrian
traffic



The INGRESS'R's contoured profile allows activation from literally any approach and height level.

ingress\`in-gres\` *n*: 1. the act of entering 2. the power or liberty of entrance or access

Wikk Industries brings you
"THE POWER OF ENTRANCE"
with the innovative

INGRESS'R

36" tall X 6" wide X 1½" deep

**A 36" Column of
Touch Activation**



A New Direction. . .

For technical information: consult the Wikk AccessAbility™ product binder, www.wikk.com or call 877-421-9490

Made in the USA



36" Column of Touch Activation The INGRESS'R®

Is it possible to unite Architectural Integrity with ADA compliance?

It's not only possible, but beautifully achievable with the INGRESS'R® by Wikk Industries, Inc.

Features and Benefits

SLEEK TAPERED PROFILE

- Deflects impact from wheeled carts and conveyances
- Naturally directs movement towards central activation column
- No squared-off edges to get caught on
- Offers vandal deterrence: no gaps or edges to pry; ABS cap is secured by spanner screws
- Weather resistant: no gaps for water or ice to penetrate

36" TALL x 6" WIDE x 1½" DEEP

(914 mm x 152 mm x 38 mm)

- Surface mounts onto walls – including uneven surfaces
- Fits precisely on commercial 6" x 6" bollard post when wall mounting is impractical

BASE DESIGN & FACTORY-INSTALLED WIRING HARNESS PROVIDE FLEXIBLE ENERGIZING OPTIONS

- 2 points of hard-wiring access from flush junction boxes
- 4" x 2" x ½" space provided beneath the ABS cap for RF transmitter; simply connect to harness

RUGGED, YET SENSITIVE

- Dependable micro-switch: 15 amp, 125/250VAC, UL® & CSA listed
- Sturdy, 1/8" extrusion (nominal) with superior finishes
- Actuates from literally all points on the activation column

STANDARD MODELS STOCKED FOR QUICK DELIVERY

- Clear Anodized Aluminum with blue wheelchair logo (model I36-5 Clear) & with added text "PUSH TO OPEN" (model I36-3 Clear)
- Dark Bronze Anodized Aluminum with white wheelchair logo (model I36-5 Dk Bz) & with added text "PUSH TO OPEN" (model I36-3 Dk Bz)
- Models without logo are available, as well as other finishes and materials



CROSS SECTION VIEW
showing
tapered profile

36" VERTICAL
ACTIVATION COLUMN

36" CONTOURED
BASE



WIRELESS
Shown with transmitter
(optional)



HARD-WIRE
Conduit access points
in base at 3" from top
and 10" from bottom



BOLLARD
MOUNTED
option

Dark
Bronze
on
Dark
Bronze
(shown)



Recommended
mounting
height is 3"
from finished
floor.

Patented design – exclusive to Wikk

...the Logical Choice

For technical information: consult the Wikk AccessAbility™ product binder, www.wikk.com or call 877-421-9490