

SQUARE Key Switch



KS-4

4 1/2" x 4 1/2" (114 x 114 mm)

- Fits 1- or 2-gang mount or prep
- Mount directly onto Wikk square bollards
- Includes dummy screws and nuts to present finished appearance

CATALOG NO.	STYLE
KS1-4 WIRELESS OPTION	1 pole, Momentary Contact
KS2-4	2 pole, Momentary Contact
KSM1-4	1 pole, Maintained Contact
KSM2-4	2 pole, DPDT Maintained Contact
KSM1-4 OOH	1 pole, Maintained Contact On/Off/Hold Open with Light
KSM2-4 OOH	2 pole, Maintained Contact On/Off/Hold Open with Light

SQUARE Maintained Key Switch and AA-3 Combination



KSM1-4XAA-3

A combination switch featuring an AA and a maintained 1 pole key switch to offer a neat, orderly solution for access and security. The 4 1/2" x 4 1/2" back-plate serves as the mounting plate, ready for flush mount directly to a double gang electrical box equipped with 2-device surface plate, or surface mount to Wikk's SURF 4/M, SURF SQ 4 & 6 BLK, and Square Bollards (requires 2-gang prep). You may choose your AA legend and the finish to customize the installation.

CATALOG NO.	STYLE
KSM1-4xAA-3	1 pole, Maintained Contact with AA-3 Switch Attached (Other AA legends may be used)

SURFACE MOUNTS for Square Key Switches

SURF SQ 4&6 BLK

4 1/2" X 4 1/2" X 1 3/4" O.D. (114 X 114 X 44 mm)
1 5/8" Inside Depth (41 mm)

SHOWN WITH
4x4 SERIES SWITCH
AND BATTERY
(Sold separately)




Black ABS box with unique battery change-out compartment. Battery can be exchanged without switch removal.

Tamper resistant: compartment door is held in place by the switch and cannot be removed or lost. Switch mounting plate is recessed, presenting a finished appearance.

Hard-Wire and Wireless




Registered design; distributed by Wikk Industries



N4X4F FLUSH MOUNT

6 3/4" X 6 3/4" X 1 7/8" O.D. (172 X 172 X 47.6 mm) 5" X 5" Inside (127 X 127 mm)
1 7/8" Inside Depth (47.6 mm)



Durable black ABS enclosure, designed for mounting flush into hollow wall. Features a molded-in 7/8" (22mm) wide trim ring and aluminum mounting bracket. Includes required gasket plate which also makes this box weather-resistant.

Hard-Wire or Wireless if mounted into RF-transparent wall materials.

N4X4S SURFACE MOUNT

5 3/8" X 5 3/8" X 1 7/8" O.D. (136.5 X 136.5 X 47.6 mm) 5" X 5" Inside (127 X 127 mm)
1 7/8" Inside Depth (47.6 mm)



4X4 switch sets flush within this durable ABS enclosure, insuring a high degree of tamper-resistance. 2 1/8" (54mm) projection. Includes required gasket plate which also makes this box weather-resistant.

Hard-Wire or Wireless

SURF 4/M

4" X 4" X 1 1/8" O.D. (102 X 102 X 29 mm) 1 1/8" Inside Depth (29 mm)

Clear or Dark Bronze Anodized Aluminum ring with plated mounting bracket.
Hard-Wire only

FEATURES:

- Heavy duty compact block and switch assembly
- 1" satin chrome mortise cylinder with Adams Rite cam and Schlage C keyway
- All locks keyed alike (Stainless switches only)
- Fully assembled with cylinder intact
- Complete parts kit includes: 2 keys, terminal connectors, stainless Phillips screws, stainless tamper-resistant screws, and set-screw wrench (for cylinder exchange)
- Rated 6 amps at 125 VAC, 3 amps at 250 VAC (1 PDT Momentary rated 5 amps at 120 VAC, 2 amps at 250 VAC)

OPTIONS:

- Decorative materials and finishes available (see page 11)
- Custom engraving upon request
- Wikk Wireless on single pole momentary switches (see page 14 for transmitters)
- May be ordered without cylinder (Add suffix "-CYL")
- On/Off/Hold Open available without light (Add suffix "-LIGHT")